## MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION 

TRADE NAME: SURE-TILE MASTIC ADHESIVE

CHEMICAL FAMILY/SYNONYMS: ACRYLIC EMULSION ADHESIVE

MANUFACTURER: W. R. BONSAL COMPANY, P.O. BOX 241148, CHARLOTTE, N. C. 28224

EMERGENCY PHONE: (704) 525-1621 Mr. Fred Goeman

-----

SECTION II - HAZARDOUS INGREDIENTS

2222222222222222				
DESCRIPTION	CAS#	PERCENT	OCCUPATIONAL EXPOSURE LIMITS TLV PEL	VAPOR PRESSURE (MM HG)
STYRENE ACRYLATE COPOL	YMER			(1991 1107
FREE MONOMER	TRACE	<0.2%	5PPM	
HYDRO CARBON RESIN		<4	5 MG/CUM	
DIBUTYL PHTALATE	84-74-2	2-1	5 MG/CUM	
PROPYLENE GYLCOL	57-55-6	2-1	LD50-20 GR/KG	
PROPRIETARY ADDITIVES		<10	5MG/CUM	
AQUA AMMONIA	7664-41-7	0.5	25PPM (CORROSIVE	)

SECTION III - PHYSICAL DATA BOILING POINT (°F) N/A SPECIFIC GRAVITY (H,O=1) 1.3-1.2 VAPOR PRESSURE (mmHq.) N/A % VOLATILE BY VOLUME (%) ₹48 VAPOR DENSITY (AIR=1) N/A EVAPORATION RATE SOLUBILITY IN WATER: SOLUBLE

APPEARANCE & ODOR: WHITE, HEAVY PASTE, ACRYLIC ODOR.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

-----

FLASH POINT: TCC >190°F TOC 190°F FLAMMABLE LIMITS

WATER

EXTINGUISHING MEDIA:

SPECIAL FIRE FIGHTING PROCEDURES: NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

245 Page 1 of 2

> Prepared By: Friedrich Goeman

JAN-90

## MATERIAL SAFETY DATA SHEET

PRODUCT: SURE-TILE MASTIC ADHESIVE				
=======================================				
SECTION V - HEALTH HAZARD DATA				
THRESHOLD LIMIT VALUE: 5 MG/CUM OR 25 PPM FOR AMMONIA.				
THRESHOLD LIMIT VALUE. 5 MG/COM OR 25 PPM FOR AMMONIA.				
EFFECTS OF OVEREXPOSURE: Can cause eye irritation. Excessive inhalation of vapors can cause headache, etc., ingestion can cause gastronomical irritati				
EMERGENCY FIRST AID: Skin: wash exposed area with soap and water. Launder contaminated clothes before reuse. Eye: flush with water for 15 minutes. G medical attention. Inhalation: move to fresh air. Consult physician. Ingestion: do not induce vomiting. Get medical attention.				
SECTION VI - REACTIVITY DATA				
STABILITY: UNSTABLE STABLE X				
INCOMPATABILITY (MATERIALS TO AVOID): Strong ozidizing agents.				
HAZARDOUS DECOMPOSITION PRODUCTS: None				
HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR _X				
SECTION VII - SPILL OR LEAK PROCEDURES				
IN CASE MATERIAL IS RELEASED OR SPILLED: Scrape up and dispose.				
WASTE DISPOSAL METHOD: Landfill in accordance with local, state and federal regulations.				
SECTION VIII - SPECIAL PROTECTION INFORMATION				
RESPIRATORY PROTECTION (TYPE): Normal ventilation should be adequate.				
Local Exhaust: Yes Special: In confined area, forced				
Other: ventilation may be needed				
OTHER PROTECTIVE CONTRACTOR EYE PROTECTION: Safety glasses w				
Clean long sleeve and long leg clothing				
SECTION IX - SPECIAL PRECAUTIONS				
PRECAUTIONS IN HANDLING AND STORING: Keep container closed when not in use.				
OTHER PRECAUTIONS: Vapors are heavier than air and could migrate to low are				
245 Page 2 of 2				
·				